

## Übersicht

Typ Bestell-Nr.	Bezeichnung	Schirmungsmaß		Verpackungs- Einheit/ Gewicht (St./kg)
<b>EMU 02</b> 273245 	F-Winkelstecker	> 90 dB		10 (100, 2000)/ 0,11
<b>EMU 03</b> 273246 	F-Doppelbuchse	> 90 dB		10 (100, 2000)/ 0,07
<b>EMU 04</b> 273244 	F-Doppelstecker	> 90 dB		10 (100, 2000)/ 0,13
<b>EMU 05</b> 273270 	F-Prüfstecker	> 90 dB		10 (100, 1000)/ 0,12
<b>EMU 06</b> 273271 	F-Übergang F (Sti) - IEC (Bu)	VHF: > 85 dB UHF: > 75 dB		10 (100, 1000)/ 0,10
<b>EMU 07</b> 273272 	F-Übergang F (Sti) - IEC (Sti)	VHF: > 85 dB UHF: > 75 dB		10 (100, 1000)/ 0,12
<b>EMU 08</b> 273273 	F-Übergang F (Bu) - IEC (Bu)	VHF: > 85 dB UHF: > 75 dB		10 (100, 1000)/ 0,12
<b>EMU 09</b> 273274 	F-Übergang F (Bu) - IEC (Sti)	VHF: > 85 dB UHF: > 75 dB		10 (100, 1000)/ 0,06
<b>EMU 12</b> 273281 	F-DC-Block (5-2400 MHz)	> 90 dB		5 (100)/ 0,06